



# HEAT & COOL

## GP SERIES 5-15 HP PORTABLE CHILLERS



AEC's GP Series offers 20-50 kW (5-15 tons of refrigeration) for their air-and-water-cooled portable chillers and provides a leaving coolant temperature range of 20°F to 80°F (-7.5°C to 30°C). Offering the smallest footprint in the industry, the GP Series is also the first product line to utilize environmentally friendly R410a refrigerant.

### STANDARD FEATURES

- Environmentally friendly, R410a refrigerant
- Branch motor circuit protection
- "Y" strainer on process water line to evaporator
- Off-the-shelf modular controller is accurate to within +/- 1°F (+/- 0.6°C)
- Easy-to-read LCD display showing system operating status, Set Point and To-Process temperature; remote mount without special configuration
- Multiple line screen, 20 character x 8 line display
- Stamped, stainless steel, horizontally mounted pump assures reliability
- Leaving water temperature range of 20°F to 80°F (-7.5°C to 30°C)
- Non-ferrous piping
- Air-cooled units feature aluminum fin tube condensers with easy on/off, washable air filters
- Water-cooled units equipped with water regulating valves with tube-in-tube condensers
- No tools necessary to access the mechanical cabinet
- 4" swivel casters with locks
- Electronic hot gas bypass valve
- Non-fused disconnect switch with single point power connection
- 1 year compressor and labor warranty; 2 year parts warranty; 3 year limited controller warranty
- NEMA 12 electrical enclosure



1100 E Woodfield Road, Suite 588  
Schaumburg, IL 60173 USA  
Tel. 847-273-7700 Fax 847-273-7804

www..com



**WHITLOCK/  
MATERIAL  
HANDLING**



**HEAT & COOL**



**BLEND &  
RECLAIM**



**NELMOR/  
GRANULATE**



**DOWNSTREAM  
EXTRUSION**



**AUTOMATE**



**SYSTEMS  
CONTRACTING**



**SERVICE**



# HEAT & COOL

## GP SERIES 5-15 HP PORTABLE CHILLERS

The magnetic connection on the controller interface allows it to be mounted anywhere on the unit. This allows the chiller to be placed anywhere on the process line since there is no front or back to the unit.



Model		20	30	40	50
Compressor		Hermetic scroll with compressor staging			
Compressor HP (kW)		5 (3.7)	7.5 (5.6)	10 (7.5)	15 (11)
Evaporator		Stainless steel brazed plate			
Reservoir gal (l)		20 (76)		40 (151)	
Pump HP (kW)		1.5 (1.1)	2 (1.5)		3 (2.2)
Height (in, mm)	GPAC	63 (1600)	81.5 (2070)	80.5 (2044)	99 (2515)
	GPWC	60.5 (1537)	60.5 (1537)	60.5 (1537)	79 (2007)
	GPRC				
Depth (in, mm.)		35 (889)		44 (1118)	
Width (in, mm.)		35 (889)			
Weight lbs (kg)	GPAC	520 (235)	700 (320)	760 (345)	950 (430)
	GPWC	550 (250)	730 (335)	790 (360)	980 (445)
	GPRC				

Contact factory for detailed information on remote condensers.



1100 E Woodfield Road, Suite 588  
Schaumburg, IL 60173 USA  
Tel. 847-273-7700 Fax 847-273-7804



**WHITLOCK/  
MATERIAL  
HANDLING**



**HEAT & COOL**



**BLEND &  
RECLAIM**



**NELMOR/  
GRANULATE**



**DOWNSTREAM  
EXTRUSION**



**AUTOMATE**



**SYSTEMS  
CONTRACTING**



**SERVICE**